



- 2,5" voice coil Kapton former and aluminium winding
- Progressive wave spider
- Cloth surround with DAR technology
- Cone waterproof treatment
- Ventilated neodymium magnet and voice coil to reduce power compression
- 96.7 dB sensitivity


Specifications	
Nominal Diameter	268mm (10")
Nominal Impedance	8Ω
Rated Power AES ⁽¹⁾	250W
Continuous Program Power ⁽²⁾	500W
Sensitivity @ 1W/1m ⁽³⁾	96.7dB
Voice Coil Diameter	65mm (2,5")
Voice Coil Winding Depth	12mm
Magnetic Gap Depth	8mm
Flux Density	1.22T
Magnet Weight	220g
Net Weight	2.2kg

Thiele & Small Parameters ⁽⁴⁾			
Re	5.42Ω	Fs	61.0Hz
Qms	5.50	Qes	0.39
Qts	0.36	Mms	33.4g
Cms	204μm/N	Bxl	13.28Tm
Vas	34.7l	Sd	346.3cm ²
X max ⁽⁵⁾	+/-3.2mm	X var ⁽⁶⁾	+/-5.7mm
η ₀	1.93%	Le (1kHz)	0.50mH

Constructive Characteristics	
Magnet	: Neodymium
Basket Material	: Aluminium Die-Cast
Voice Coil Winding Material	: Aluminium
Voice Coil Former Material	: Kapton
Cone Material	: Paper
Cone Treatment	: Surface Waterproof Treatment
Surround Material	: Treated Cloth
Dust Dome Material	: Solid Paper



Frequency Response on IEC Baffle (DIN 45575) @ 1W,1m – Free Air Impedance



- Note:
- 1 : Rated Power measured with 2 hours test with pink noise signal, 6dB crest factor, loudspeaker mounted on enclosure
 - 2: Power on Continuous Program is defined as 3 dB greater than the Rated Power
 - 3: Calculated by Thiele & Small parameters
 - 4: Thiele & Small parameters measured with laser system without preconditioning test
 - 5: Measured with respect to a THD of 10% using a parameter-based method
 - 6: Value corresponding to a decay of the Force Factor, or Compliance, or both, equal to the 50% of the small signal value.
 - 7: Drawing dimensions: mm
 - 8: The notch around 400Hz on the frequency response is typical of the measurement on IEC baffle